

## HOSE REEL HIGH PRESSURE NOZZLE

### TECHNICAL DATA:-

1. CONTINUOUS FLOW-RATE ADJUSTMENT BETWEEN 0-150 l / MIN
2. CONTINUOUS JET ADJUSTMENT BETWEEN FULL JET, FLAT JET AND SPRAY JET.
3. APPROX. 25M AT 150 l / MIN AND WITH A 40 BAR FULL JET.
4. 3 / 4" BSP MALE THREADED CONNECTOR FOR HOSE COUPLING.
5. WEIGHT 3KG
6. COLOR :- RED & BLACK



### DESIGN:-

1. ANODIZED LIGHT-ALLOY CASTING WITH RUBBER HANDLE AND ADJUSTING LEVER.
2. INTERIOR PARTS MADE OF STAINLESS STEEL.
3. ROTATING BALL-BEARING TYPE HOSE CONNECTOR MADE OF STAINLESS STEEL.

### PRACTICAL ADVANTAGE:-

1. THE IDEAL EQUIPMENT FOR COMBATING FIRES INSIDE BUILDINGS, INCIPIENT FIRES AND FOREST FIRES.
2. IS EXTREMELY HANDY IN USE AND CONSUMES VERY LITTLE WATER, YET HAS ENORMOUS COMBAT POWER AND EXTINGUISHING AND COOLING EFFECTIVENESS.
3. MAXIMIZES "CLING-EFFECT" OF HEAVY FOAM CARPETING ON VERTICAL SURFACES.